


RECOMMENDED PC BOARD LAYOUT  
TOLERANCE: ±0.05[TOP VIEW]

- NOTES
- MATERIAL & FLASH/PLATED
  - HOUSING: HIGH TEMP. THERMOPLASTIC+GLASS FIBRE  
[UL 94V-0], COLOR: BLACK
  - TERMINAL: COPPER ALLOY  
PLATED; GOLD FLASH ON CONTACT AREA.  
GOLD FLASH ALL OVER  
BASE NICKEL: 50μ"
  - COVER: HIGH TEMP. THERMOPLASTIC+GLASS FIBRE  
[UL 94V-0], COLOR: BLACK
  - PACKAGE: TAPE/REEL



UNITS: mm		<b>CSCONN</b>		SHENZHEN CSCONN PRECISE ELECTRONICS CO.,LTD		
GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE:		
X. ° ±5°	0.X±0.3	CBA-220493-21		BATTERY 4P 2.2MM H=2.1MM		
X. 1±2°	0.XX±0.2	APPD:		DWG NO.		
XX. ±1°	0.XXX±0.1	CHKD: Skila		BATTERY		
XXX. ±0.5°		DR: Kitty		SCALE	SHEET	REV
				1:1	1 OF 1	A