



- NOTES:
- 1) MATERIAL:
 - 1-1 HOUSING: THERMOPLASTIC; UL 94V-0, COLOR: BLACK
 - 1-2 CONTACT: COPPER ALLOY T=0.10mm
 - 1-3 NAIL: STAINLESS STEEL, T=0.20mm
 - 2) FINISH:
 - 2-1 CONTACT: GOLD 5u" PLATING ON CONTACT AREA (SEE P/N)
 - 2-2 NAIL: 50u" MIN NICKEL UNDERPLATING OVER ALL
 - 2-3 NAIL: 100~200u" Tin OVERALL
 - 3) PRODUCT SPECIFICATIONS:
 - 3-1 VOLTAGE RATING: 250V
 - 3-2 CURRENT RATING: 2.0A
 - 3-3 INSULATION RESISTANCE: 1000MEG OHM MIN
 - 3-4 CONTACT RESISTANCE: 50 MILLIOHM MAX
 - 3-5 OPERATION TEMPERATURE: -55° TO +125°
 - 3-6 DURABILITY: 3000 CYCLES
 - 3-7 NORMAL FORCE: 80gf MIN AT THE WORKING POSITION

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO., LTD	
GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE:	
X. ± 5°	0. X ± 0.25	CBA0323212001		BATTERY 3P 2.5MM H=3.2MM 沉板式	
X.1 ± 2°	0. XX ± 0.2	APPD:		DWG NO.	
XX ± 1°	0. XXX ± 0.1	CHKD: SK11a		BATTERY	
		DR: Kitty		SCALE	SHEET
				1:1	1 OF 1
					REV
					A