



PART NO.	H=?	DIM A	DIM B
CBA03254354001	5.4	5.4	3.9
CBA03254360001	6.0	6.0	4.5
CBA03254365001	6.5	6.5	5.0
CBA03254370001	7.0	7.0	5.5
CBA03254375001	7.5	7.5	6.0
CBA03254380001	8.0	8.0	6.5

Bill of Materials:

No.	TITLE	MATERIAL	FINISH(OR COLOR)
1	HOUSING	LCp+30%GF UL94 V-0	BLACK
2	TERMINAL	BeCu, T=0.15mm	GLOD 5u" PLATED
3	GROUND SLICE	C2889R-H, T=0.20mm	TIN PLATED

RECOMMENDED PCB LAYOUT  
TOP VIEW (.XX±0.05)

- SPECIFICATIONS:
- CURRENT RATING: 2.0A 12V AC/DC.
  - CONTACT RESISTANCE: 30mΩ MAX AT DC 20mA.
  - INSULATION RESISTANCE: 500MΩ MIN AT 500V DC.
  - OPERATING TEMPERATURE RANGE: -40°C TO +85°C.

UNITS: mm		<b>CSCONN</b>		CSCONN PRECISE ELECTRONICS CO., LTD	
GENERAL TOLERANCE					
X. ° ±5°	0. X ±0.3	PART NO. (INTENDED USE)	TITLE: BATTERY 3P 2.5MM H=5.4-8.0MM 带柱		
X. 1 ±2°	0. XX ±0.2	CBA03254380001	DWG NO. BATTERY		
XX. ±1°	0. XXX ±0.1	APPD:	SCALE SHEET REV		
XXX. ±0.5°		CHKD: Skilja	1:1 1 OF 1 A		
		DR: Kitley			