



PCB LAYOUT

PART NO.	A	B
CBA3103884877	7.70	5.40
CBA3103884868	6.80	4.50

- NOTES:**
- Material:
 - Insulator: High temperature thermoplastic UL94V-0, (BLACK LCP)
 - Beryllium copper: Plating, gold(3-8U") over nickel(50-80U")
 - Pho Bronze: Plating, Tin(100-120U") over nickel(50-80U")
 - Electrical specifications:
 - Voltage rating: 12 VAC
 - Current rating: 2.0A
 - Dielectric strength: 250V AC for 1 minute
 - Insulation resistance: 500 MΩ
 - Contact resistance: 50 MΩ
 - Operation temperature: -40 °C to +105 °C
 - MAX. processing temp: 260 °C for 30 seconds
 - Mechanical specifications:
 - Durability: 5000 cycles

CSCONN

UNITS: mm		GENERAL TOLERANCE	
X.° ±5°	0.X ±0.3	PART NO. (INTENDED USE)	CSCONN PRECISE ELECTRONICS CO., LTD
X.1 ±2°	0.XX ±0.2	APPD:	TITLE: BATTERY 3P 3.1MM H=XMM
XX ±1°	0.XXX ±0.1	CHKD: SKI1a	DWG NO. BATTERY
XXX ±0.5°		DR: K1tty	SCALE 1:1
			SHEET 1 OF 1
			REV A