



RECOMMEND P.C.B LAYOUT
TOLERANCE ± 0.05
TOP VIEW

- MATERIALS**
1. HOUSING: HI-TEMP.
 2. TERMINAL: COPPER ALLOY (T=0.20mm), GOLD PLATED OVER NICKEL.
 3. SHELL: STAINLESS STEEL (T=0.20mm) SPECIFICATION
 1. CURRENT RATING: 1.5 A. MAX
 2. DIELECTRIC WITHSTANDING VOLTAGE: 500V A.C. R.M.S. FOR ONE MINUTE.
 3. INSULATION RESISTANCE: 500M Ω MIN. AT 250V DC.
 4. CONTACT RESISTANCE: 100m Ω MAX
 5. OPERATING TEMPERATURE: -40°C TO +105°C
 6. CONTACT FORCE: 1.60gf/min WHEN STROKE OF 1.5mm
 7. HOUSING BROKEN FORCE 2.0KG/min
- PACKAGE: TAPE/REEL

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO., LTD	
GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE:	
X. ° ±5°	0. X ±0.3	CBA65038602001		BATTERY 3P 6.5MM H=8.6MM	
X. 1 ±2°	0. XX ±0.2	APPD:		DWG NO.	
XX. ±1°	0. XXX ±0.1	CHKD: Skilla		BATTERY	
XXX. ±0.5°		DR: Kitty		SCALE SHEET REV	
				1:1 1 OF 1 A	