



SPECIFICATION

1. Rating : DC 16V 3. 5A;
2. Contact resistance: $\leq 0.03\Omega$;
3. Insulation resistance: $\geq 100M\Omega$ (DC250V) ;
4. Withstand voltage: 500VAC ;
5. Insertion and extraction force: 3-20N;
6. Life test: 5, 000 cycles.

No.	PART NAME	QTY	MATERIAL (THICK, COLOR)	REMARK
③	HOUSING	1	PA9T (Black)	
①	PIN	1	BRASS	CuSn-Plated
②	TERMINAL	1	BRASS t=0.25	Ag-Plated
②	TERMINAL	1	SUS301 t=0.2	Ag-Plated
①	TERMINAL	1	BRASS t=0.3	Ag-Plated

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO.(INTENDED USE)		TITLE: DC JACK	
X. ° ±5°	0.X±0.3	CDC0509		DWG NO. JACK	
X.1 ±2°	0.XX±0.2	APPD:		SCALE SHEET	
XX ±1°	0.XXX±0.1	CHKD: Skilla		1 OF 1	
XXX ±0.5°		DR: Kitty		REV	
				A	