



Voltage Rating : 50V AC/DC
 Current Rating : 0.4A AC/DC
 Withstand Voltage : 500V AC/minute
 Contact Resistance : 30mΩ(MAX.)
 Insulation Resistance : 100MΩ(MIN.)
 Temperature Range : -55°C~+85°C

Dimensional Information:

Part No.	Dimensions			
	A	B	C	D
4P	4.00	1.50	2.57	3.40
5P	4.50	2.00	3.07	3.90
6P	5.00	2.50	3.57	4.40
8P	6.00	3.50	4.57	5.40
10P	7.00	4.50	5.57	6.40
12P	8.00	5.50	6.57	7.40
14P	9.00	6.50	7.57	8.40
16P	10.00	7.50	8.57	9.40
18P	11.00	8.50	9.57	10.40
20P	12.00	9.50	10.57	11.40
22P	13.00	10.50	11.57	12.40
24P	14.00	11.50	12.57	13.40
26P	15.00	12.50	13.57	14.40
28P	16.00	13.50	14.57	15.40
30P	17.00	14.50	15.57	16.40
32P	18.00	15.50	16.57	17.40
34P	19.00	16.50	17.57	18.40
38P	21.00	18.50	19.57	20.40
40P	22.00	19.50	20.57	21.40
45P	24.50	22.00	23.07	23.90
50P	27.00	24.50	25.57	26.40

UNITS: mm

CSCONN

CSCONN PRECISE ELECTRONICS CO.,LTD

GENERAL TOLERANCE

X. ° ±5° 0.X±0.25

X.1±2° 0.XX±0.2

XX. ±1° 0.XXX±0.1

PART NO.(INTENDED USE)

CPF0510XX390

TITLE: FPC 0.5MM XP H=1.0MM 前插后掀

DWG NO. FPC

CHKD: Skila

DR: Kitty



SCALE SHEET REV

1:1 1 OF 1 A