



SPECIFICATION
 1.Material:
 Housing: HIGH-TEMP Plastic:UL94V-0,color:Natural.
 Lock: HIGH-TEMP Plastic:UL94V-0,color:black.
 Contacts: Copper alloy.
 Solder tab: Copper alloy.
 2.Electrical Characteristics:
 Current rating: 0.5A(max).
 Voltage rating: 50V(max).
 Operating temperature: -25°C~+85°C.
 Insulation resistance: 500M ohms min. at 500V DC
 Dielectric withstanding voltage: 500V AC/minute.
 Contact resistance: 30m ohms max.

APPLICABLE FCC
 TOLERANCE:±0.05

PIN NO.	DIM. A	DIM. B	DIM. C
04	8.60	3.00	5.07
05	9.60	4.00	6.07
06	10.60	5.00	7.07
07	11.60	6.00	8.07
08	12.60	7.00	9.07
09	13.60	8.00	10.07
10	14.60	9.00	11.07
11	15.60	10.00	12.07
12	16.60	11.00	13.07
13	17.60	12.00	14.07
14	18.60	13.00	15.07
15	19.60	14.00	16.07
16	20.60	15.00	17.07
17	21.60	16.00	18.07
18	22.60	17.00	19.07
19	23.60	18.00	20.07
20	24.60	19.00	21.07
21	25.60	20.00	22.07
22	26.60	21.00	23.07
23	27.60	22.00	24.07
24	28.60	23.00	25.07
25	29.60	24.00	26.07
26	30.60	25.00	27.07
27	31.60	26.00	28.07
28	32.60	27.00	29.07
29	33.60	28.00	30.07
30	34.60	29.00	31.07
31	35.60	30.00	32.07
32	36.60	31.00	33.07
33	37.60	32.00	34.07

RECOMMEND PCB LAYOUT

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE:	
X. ° ±5°	0.XX±0.25	CFP1015XX01002		PFC 1.0MM XP H=1.5MM 掀盖式	
APPD:		CHKD:		DWG NO.	
X.X ±1°		0.XXX±0.1		RPP	
DR:		Kitty		SCALE	
				1:1	
				SHEET	
				1 OF 1	
				REV	
				A	