



RECOMMENDED PCB LAYOUT THICKNESS = 1.6 mm
TOLERANCE:±0.05

- NOTE:
1. MATERIALS AND FINISHED INSULATOR : LCP UL-94V0, COVER:LCP UL-94V0 SHELL : BRASS, NI FINISHED CONTACT MATERIAL : BRASS, SELEVITE GOLD FINISHED
 2. ELECTRICAL CHARACTERISTICS CONTACT CURRENT RATING : 0.5 AMPS CONTACT RESISTANCE : 20 MILLIOMHS MAX. DIELECTRIC WITHSTANDING VOLTAGE : 500 V AC/MIN. INSULATION RESISTANCE : 100 MEGAOHMS MIN.
 3. MECHANICAL MATING FORCE: 4.5Kgf MAX. UNMATING FORCE: 1.0 KgF MIN
 4. ENVIRONMENTAL TEMPERATURE RATING : -55° C ~ +105° C

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO.(INTENDED USE)		TITLE:	
X. ±5°	0. X±0.25	CHD051915041001		HDMI 19P FEMALE SMT 立插	
X. 1±2°	0. XX±0.2	APPD:		DWG NO.	
XX. ±1°	0. XXX±0.1	CHKD: Skilla		HDMI	
		DR: Kitty		SCALE	SHEET
				1:1	1 OF 1
					REV
					A