



Bill Of Materials:

No.	TITLE	MATERIAL	FINISH(OR COLOR)	QTY
1	SHELL	黃銅 (C2680R+H), T=0.50mm	NICKEL PLATED	1
2	HOUSING	LCP+30%GF, UL94 V-0	BLACK	1
3	TERMINAL-(19支)	磷銅 (C5210R+H), T=0.20mm	1 $\mu$ r GL/OD/TIN PLATED	9
4	TERMINAL-2(10支)	磷銅 (C5210R+H), T=0.20mm	1 $\mu$ r GL/OD/TIN PLATED	10

- SPCCIFICATIONS:
- ELECTRICAL CHARACTERISTICS:
    - CONTACT CURRENT RATING: 0.5A Min.
    - VOLTAGE RATING: 40V AC.
    - CONTACT RESISTANCE: 30m $\Omega$  Max.
    - INSULATION RESISTANCE: 100M $\Omega$  Min.
    - DIELECTRIC STRENGTH: 500V AC/3 minute.
  - MECHANICAL:
    - INSERTION FORCE: 4.4 kgf Max.
    - WITHDRAWAL FORCE: 0.98 kgf Min.
    - RETENTION FORCE: 600gf Min/Pin
  - ENVIRONMENTAL:
    - OPERATING TEMPERATURE: -25°C TO +85°C
  - DIM. MARKED ①②③... SHOULD BE CONTROLLED BY QC

**CSCONN**

CSCONN PRECISE ELECTRONICS CO., LTD

PART NO.(INTENDED USE)

CHD051915061F

TITLE: HDMI 19P/F 无耳

APPD:

SK: 11a

DWG NO.

HDMI



SCALE

SHEET

REV

DR: Kitty

1:1

1 OF 1

A

E 1 2 3 4 5 6 7 8 E