



Notes:

1. Materials:

- 1.1 Housing: High temperature thermoplastic with g.f.i, UL94 v-0.
- 1.2 Contact: copper alloy,t=0.20mm.
- 1.3 Shell: copper alloy,t=0.25mm.

2. Specifications:

- 2.1. Current rating: 1 A Max.
- 2.2. Dielectric withstanding:voltage: 100 V(ac) for 1 min.
- 2.3. Contact resistance: 50 mW Max.
- 2.4. Insulation resistance: 100 MW Min.
- 2.5. Total mating force: 3.57 Kgf Max.
- 2.6. Total unmating force: 1.0 Kgf Min,0.81~2.05 Kgf Min,after 10000 Insertion/extraction cycles
- 2.7. Temperature range: -30° C~+80° C

UNITS:		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO.(INTENDED USE)		TITLE:	
X. ° ±5°	0. XX±0.25	CML0065802001		MICRO USB 5P B TYPE 前插后贴	
X. 1±2°	0. XX±0.2	APPD:		DWG NO.	
XX. ±1°	0. XXX±0.1	CHKD: Skila		MICRO USB	
		DR: Kitty		SCALE	
				1:1	
				SHEET	
				1 OF 1	
				REV	
				A	