



PCB LAYOUT

SPECIFICATIONS

Current Rating : 1AMP
 Operation Temperature: -40°C to +105°C
 Contact Resistance : 20mΩ Max.
 Insulation Resistance: 1000MΩ Min.
 Withstanding Voltage : AC 500V
 Insulator Material : Polyester(UL94V-0)
 Standard: Nylon-6T
 Contact Material : Brass
 Contact plating : Au or Sn Over 50u”
 Ni

UNITS: mm	CSCONN	CSCONN PRECISE ELECTRONICS CO.,LTD
-----------	---------------	------------------------------------

GENERAL TOLERANCE	PART NO. (INTENDED USE)	TITLE:
-------------------	-------------------------	--------

X. ° ± 5°	0. X ± 0. 25	CPH1270261X003	PH 1. 27MM XP SMT双排型高1. 6MM H6. 1MM
-----------	--------------	----------------	-------------------------------------

X. 1 ± 2°	0. XX ± 0. 2	APPD:	DWG. NO.
-----------	--------------	-------	----------

XX. ± 1°	0. XXX ± 0. 1	CHKD:	PH
----------	---------------	-------	----

DR:	Kitty	SCALE	SHEET	REV
-----	-------	-------	-------	-----

1:1	1 OF 1	A
-----	--------	---

PH	1:1	1 OF 1	A
----	-----	--------	---

PH	1:1	1 OF 1	A
----	-----	--------	---