



TECHNICAL CHARACTERISTICS

1. General characteristics
 - Contact principle: Friction technology
 - Operating position: Shaft up/down/horizontal
 - Mounting System : Smt (Post Optional)
 - Durability: 5000 cycles min.
2. Mechanical characteristics:
 - Insulation material : Thermoplastic ,UL 94v-0
3. Electrical Characteristics
 - Number of contacts (Optional): 6pins or 8pins
 - Contact resistance: 50mΩ initial, 100mΩ max
 - Insulation resistance : >1000MΩ / 500V DC
4. Solder ability
 - Wave: Not applicable
 - Vaporphase: 215°C, 30sec. Max
 - IR reflow: 250°C, 15sec. Max
5. Environmental Characteristics
 - Manual soldering: 360°C, 3sec. Max
 - Operating temperature :-40°C ~ +85°C
 - Operating humidity: 10% ~ +95%RH
 - Storage temperature: -40°C ~ +85°C
 - Storage humidity: 10% ~ +95%RH
 - Thermal shock: -40°C ~ +85°C, 5cycles.
 - Damp heat: 40°C, 90%RH, 10days.
 - Salt-mist: 35°C, 5%NaCl, 24H

UNITS: mm		CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO.(ATTENDED USE)		TITLE:	
X ± 1°	0.X ± 0.25	CS106291726003		SIM CARD 6P H=2.6MM 掀盖式	
X ± 2°	0.X ± 0.2	APPD:		DWG NO.	
X ± 1°	0.XX ± 0.1	CHKD:		SIM CARD	
		DR:		SCALE SHEET REV	
		Skila		1:1 1 OF 2 A	
		Kitty			