


Reference dimension for PCB layout

PART NO.	H	A
CS110212835001	350	210mm
CS110212814001	140	0.00mm

TECHNICAL CHARACTERISTICS

- General Characteristics
 - Dimensions: 28.70LX17.50WX3.0 mm
 - Weight: Approx.0.70±0.1g
 - Durability: 100,000 cycles min.
- Electrical Characteristics
 - Contact resistance: 50mΩ typical,100mΩ max
 - Insulation resistance: >1000MΩ/500V DC
- Solderability
 - IR reflow: 250°C,5sec,Max
 - Manual soldering: 370°C,3sec,Max
- Environmental Characteristics
 - Operating temperature: -40°C~+85°C
 - Operating humidity: 10%~+95%RH



ITEM	PART NAME	Q'TY	MATERIAL	FINISH
1	BASE	1	Hi-temp Thermoplastic	Black UL94V-0
2	DATA CONTACT	8	Copper Alloy	Contact area:Gold plated
3	SWITCH CONTACT 2	1	Copper Alloy	Contact area:Gold plated
4	SWITCH CONTACT 1	1	Copper Alloy	Contact area:Gold plated

CSCONN

CSCONN PRECISE ELECTRONICS CO.,LTD


UNITS: mm	
GENERAL TOLERANCE	
X. ° ±5°	0. X ± 0.25
X. 1 ± 2°	0. XX ± 0.2
XX. ± 1°	0. XXX ± 0.1

TITLE: SMART CARD 8+2P H=XMM 右耳

APPD:

DWG NO. SMART CARD

CHKD: Skilla



SCALE SHEET REV

DR: Kitty



1:1 1 OF 1 A