


Specifications:

- 1. Material:**
- 1.1. Housing: Thermoplastic, UL94V-0
 - 1.2. Contact: Copper Alloy Au plated on contact area
Au plated on Solder tail Ni plated Overall
 - 1.3. SHELL: SUS, plated Au or Ni underroll
 - 1.4. Spring: SUS
 - 1.5. Slider: Thermoplastic
 - 1.6. Drawbar: SUS
- 2. Electrical:**
- 3.1. Current Rating: 0.5 A
 - 3.2. Contact Resistance: 100mΩ max
 - 3.3. Dielectric Withstanding Voltage: 500V AC
 - 3.4. Insulation Resistance: 1000MΩ MIN
- 3. Environment characteristics:**
- 1. Operating Temperature: -20°C~+60°C
- 4. Mechanical**
- 4.3. Durability: 5000 cycles

PIN NO.	PIN ASSIGNMENT
P1	DATA2
P2	CD/DATA3
P3	CMD
P4	VDD
P5	CLK
P6	VSS
P7	DATA0
P8	DATA1



RECOMMEND P.C.B LAYOUT
(General tolerance ±0.05)

CSCONN

CSCONN PRECISE ELECTRONICS CO.,LTD

UNITS: mm

GENERAL TOLERANCE

X. ±5° 0.1±0.25

X.1±2° 0.XX±0.2

XX ±1° 0.XXX±0.1

PART NO.(INTENDED USE)

CTP081312802005

TITLE:

T-FLASH CARD PUSH PUSH H=1.28MM

DWG NO.

SIM CARD

SCALE

1:1

SHEET


1 OF 1

REV

A

CHKD: SKIla

DR: Kitty



SCALE

1:1

SHEET

1 OF 1

REV

A