



- 技术指标:
- 1、塑件表面应光洁、无毛刺、明显收缩、嵌帽、裂纹等现象;
  - 2、温度范围: -25°C~85°C;
  - 3、额定电压: 200V, AC, DC(等效);
  - 4、接触电阻: ≤0.03Ω;
  - 5、绝缘电阻: ≥1000MΩ;
  - 6、耐压: 1000V, AC/minute.

PART NO	Dimensions	
	A	B
2X5 PIN	5.00	12.15
2X7 PIN	7.50	14.65
2X10 PIN	11.25	18.40
2X15 PIN	17.50	24.65
2X20 PIN	23.75	30.90

序号	名称	材料	数量	附注
1	盖帽	PA9T(U94V-0)	1	转接板材料
2	嵌帽	磷青铜	2	嵌帽材料: 磷青铜30V PIN, 厚度0.30mm
3	嵌帽	磷青铜	2	嵌帽材料: 磷青铜30V PIN, 厚度0.30mm
4	嵌帽	磷青铜	2	嵌帽材料: 磷青铜30V PIN, 厚度0.30mm

UNITS: mm		<b>CSCONN</b>		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE		PART NO. (INTENDED USE)		TITLE: WAFER 1.25MM 2*XP 立贴	
X. ±5°	0.XX±0.25	CWF-12502XL-T		DWG NO. WAFER	
X.1±2°	0.XX±0.2	APPD:		SCALE	
XX. ±1°	0.XXX±0.1	CHKD: Skilla		SHEET	
		DR: Kitty		REV	
				1:1	
				1 OF 1	
				A	

PCB Layout