


Pin位	A	B	C
2	0.8	1.85	3.85
3	1.6	2.65	4.65
4	2.4	3.45	5.45
5	3.2	4.25	6.25
6	4	5.05	7.05
7	4.8	5.85	7.85
8	5.6	6.65	8.65
9	6.4	7.45	9.45
10	7.2	8.25	10.25
11	8	9.05	11.05
12	8.8	9.85	11.85
13	9.6	10.65	12.65
14	10.4	11.45	13.45
15	11.2	12.25	14.25
16	12	13.05	15.05
17	12.8	13.85	15.85
18	13.6	14.65	16.65
19	14.4	15.45	17.45
20	15.2	16.25	18.25
21	16	17.05	19.05
22	16.8	17.85	19.85
23	17.6	18.65	20.65
24	18.4	19.45	21.45

SPECIFICATION

- Material: HIGH-TEMP Plastic, UL94V-0, color: Natural.
Housing: Copper alloy.
Contacts: Copper alloy.
Solder tab: Copper alloy.
- Electrical Characteristics:
Current rating: 0.5A(max).
Voltage rating: 50V(max).
Operating Temperature: -25°C~+85°C.
Insulation resistance: 100M ohms min. at 500V DC
Dielectric withstanding voltage: 500V AC/minute.
Contact resistance: 30m ohms max.



PCB Layout

UNITS: mm	CSCONN		CSCONN PRECISE ELECTRONICS CO.,LTD	
GENERAL TOLERANCE	PART NO. (INTENDED USE)	TITLE:	DWG NO. WAFER	
X. ° ±5°	CWF08XX172001	WAFER 0.8MM XP 贴片		
X.1 ±2°	APPD:		SCALE	SHEET
XX. ±1°	CHKD: Skila		1:1	1 OF 1
	DR: Kitty			REV
				A