



嵌合状态

剖面 A-A

PCB Layout

**SPECIFICATION**  
 1. Material:  
 Housing: HIGH-TEMP Plastic, UL94V-0, color: Natural.  
 Contacts: Copper alloy.  
 Solder tab: Copper alloy.  
 2. Electrical Characteristics:  
 Current rating: 1A(max).  
 Voltage rating: 200V(max).  
 Operating Temperature: -25°C~+85°C.  
 Insulation resistance: 1000M ohms min. at 1000V DC  
 Dielectric withstanding voltage: 1000V AC/minute.  
 Contact resistance: 30m ohms max.

接触 pole	A	B	C
2	1.25	3.85	5.75
3	2.5	5.1	7
4	3.75	6.35	8.25
5	5	7.6	9.5
6	6.25	8.85	10.75
7	7.5	10.1	12
8	8.75	11.35	13.25
9	10	12.6	14.5
10	11.25	13.85	15.75
11	12.5	15.1	17
12	13.75	16.35	18.25
13	15	17.6	19.5
14	16.25	18.85	20.75
15	17.5	20.1	22
18	21.25	23.85	25.75
20	23.75	26.35	28.25

UNITS: mm	<b>CSCONN</b>			CSCONN PRECISE ELECTRONICS CO., LTD		
GENERAL TOLERANCE	PART NO. (INTENDED USE) CWP125425XX001			TITLE: WAFER 1.25MM XP H=4.25MM 贴片		
X. ° ±5°	0. X ±0.25	APPD:	Skilla	DWG NO.	WAFER	SCALE
X. 1±2°	0. XX ±0.2	CHKD:	Kitty			
X. ±1°	0. XXX ±0.1	DR:				SHEET
						1 OF 1
						REV
						A

